



Cursa Hydraulic Oil

Dyna-Plex 21C® Cursa Hydraulic Oils are high quality, extra inhibited oils designed with hydrocracked Group II base oil, for use in multi-functional applications where long oil life is required. These oils will give you steady, reliable performance as a hydraulic medium. The hydraulic oils also demonstrate excellent compatibility with other major brands of hydraulic oils, including the MOBIL DTE numbered series.

Dyna-Plex 21C Cursa Hydraulic Oils have been finely filtered to remove external contamination and contain special O-ring conditioners to prolong hydraulic component life. Seal swell agents have been added to prevent leaks and Cursa's demulsibility characteristics enhance separation and removal of water. These oils will supply 5,000 hours of service before extreme oxidation problems occur and also provide excellent resistance to foaming, rust and wear.

<u>PROPERTY</u>	<u>ASTM TEST METHOD</u>	<u>ISO 22</u>	<u>ISO 32</u>	<u>ISO 46</u>	<u>ISO 68</u>	<u>ISO 100</u>
Viscosity @ 40°C, cSt	D-445	22.10	31.20	46.07	68.10	101.29
Viscosity @ 100°C, cSt	D-445	4.35	5.25	6.81	8.80	11.5
Viscosity Index	D-2270	100	98	100	100	100
Flash Point, COC, °C	D-92	200	216	221	227	243
Flash Point, COC, °F	D-92	392	420	430	440	470
Pour Point, °C (°F)	D-97	-42 (-44)	-40 (-40)	-40 (-40)	-33 (-21)	-30 (-22)
Color	D-1500	1.0	1.0	1.0	1.5	1.5
Gravity, °API	D-287	34.0	32.6	31.1	30.7	30.4
Turbine Oil Oxidation	D-943	5000+	5000+	5000+	5000+	5000+
Copper Strip	D-130	1b	1b	1b	1b	1b
Rust Test	D-665	Pass	Pass	Pass	Pass	Pass
Vane Pump, mgs wt loss	D-2882	12	12	12	12	12
Usable Temperature Range, °F		-10-50	-5-50	10-90	20-100	30-115
Maximum Hyd. Temperature, °F		150	150	195	200	215
Dielectric Strength, kv		35	35	35	35	35
RBOT, minutes	D-2272	950	950	950	950	950
Demulsibility	D-1401	40-40-0(5)	40-40-0(5)	40-40-0(5)	40-40-0(5)	40-40-0(5)

Meets or exceeds the following tests and requirements:

AFNOR E 48-603

ASTM D6158 HL, HM, HMHP

B.F. Goodrich – 0152

Bosch Rexroth – RDE 90235

Fives Cincinnati – P-68, P-69, P-70 (light hydraulic oils)

Danieli – 0.000.001 Type 10 & 11

DIN – 51524, Part 1 HL, Part 2 HLP

Eaton Brochure – 03-401-2010, EFDGN-TB002-E

Eaton Vickers – I-286-S, M-2950-S, 35VQ25

FMC – High-Performance Hydraulic Oil

Ford – M-6C32

General Motors – LH-04-1, LH-06-1, LH-15-1, LS-2

ISO 11158 HL, HM

Jeffrey – #87

Lee Norse 100-1

Parker Denison – HF-0, HF-1, HF-2

Racine – Model S, variable volume vane pump

SAE MS 1004

U.S. Steel – 136, 127, 126

ZF – TE-ML 07H, TE-ML 21M

HO-1/07.13.23